## Annual Toilet Room Facilities for Early Intervention, Pre-Kindergarten and Kindergarten Classrooms 2025-2026 School Year

## ONE FORM PER SCHOOL BUILDING

District/ County: Township of Union/Union School: Franklin	Elementary School	
List Room(s) Number/Name: Room 5, 7, 9, 11		
<ul> <li>Our school district elects to use the alternate method of compliance 6A:26-6.3. In lieu of individual toilet rooms in each classroom, toilet adjacent to or outside the classroom, if the following criteria are satis</li> <li>No child or group of children shall be left unsupervised at any time facilities. Provisions shall be made for adult supervision in a manner instructional time;</li> <li>Toilet facilities shall be readily accessible and the toilet room and schild from the classroom door;</li> <li>Toilet facilities shall be provided for both boys and girls and shall in NJAC 6A:26-6.3(h)4ii.</li> </ul>	rooms may be provided sfactorily addressed: when traveling to or from the er that will not infringe upon signage shall be visible to the	
District alternate method of compliance pursuant to N.J.A.C. 6A:26-6  The classroom teacher, assistant, and/or supervising staff mer students traveling to/from the restrooms in the hallways.	, ,	
Board of Education has approved this alternate method of compliance.	ce on Date	
****Attach Copy of Board Resolution****		
I certify that all requirements of N.J.A.C. 6A:26-6.3 and/or 6.4 have t	peen met.	
Superintendent of Schools:	Date:	
School Business Administrator:	Date:	

Not Approved: \_\_\_\_

	_	
Executive County Superintendent		Date

## NJAC 6A:26-6.3 (h) 4

- 4. Toilet facilities for preschool and kindergarten classrooms shall be provided as follows:
  - i. An individual toilet room shall be provided in each classroom and shall meet the following criteria:
    - (1) Be located and equipped in such a way as to ensure privacy for the students; (2) Be accessible to physically disabled students and barrier free in design as per N.J.A.C. 5:23-7; 115
    - (3) Be equipped with an open front seat with a flood rim height no greater than 14 inches from the floor, and a lavatory (sink) with a flood rim height no greater than 26 inches from the floor.
  - ii. In lieu of providing an individual toilet room in each classroom as required in (h)4i above, toilet rooms may be provided adjacent to or outside the classroom if the following criteria are satisfactorily addressed:
    - (1) **No child or group of children shall be left unsupervised** at any time when traveling to or from the facilities. Provisions shall be made for adult supervision in a manner that will not infringe upon instructional time;
    - (2) <u>Toilet facilities shall be readily accessible</u> and the toilet room and signage shall be visible to a child from the classroom door;
  - (3) Toilet facilities shall be provided for both boys and girls and shall <u>meet</u> the requirements of (h)4i(4) above.
  - iii. If a school district chooses to provide toilet rooms adjacent to or outside the classroom in conformance with (h)4ii above, the chief school administrator shall certify to the executive county superintendent on forms prescribed by the Commissioner how the alternate method of compliance shall be addressed. The completed form and a copy of a resolution by the district board of education approving the alternate method of compliance shall be submitted to the executive county superintendent for approval. Thereafter, the chief school administrator annually shall resubmit the form certifying how the alternate method of compliance will be addressed. Any changes to the approved alternate method of compliance shall be submitted to the executive county superintendent for approval;